

| Feature | APPLAUD | CHARMY | ADMIRE | RESPECT |
|--------------------|---------------------------------------|---|--|---------------------------------------|
| Type | Framer/Gobo | Variable Beam | Variable Beam | Spot |
| Light Source | Tunable White LED Engine | Tunable White LED Engine | Tunable White LED Engine | Tunable White LED Engine |
| Rated Power | 20W | 33W | 20W | 20W |
| Luminous Flux | Min. 1000 lumen Typical 1200 lumen | Min. 2000 lumen Typical 2400 lumen | Min. 1000 lumen Typical 1200 lumen | Min. 1000 lumen Typical 1200 lumen |
| CCT Tunable Range | 2800K - 5600K | 1800K - 5200K | 2800K - 5600K | 2800K - 5600K |
| CRI | ≥94 | ≥95 (from 3200K to 5200K) | ≥94 | ≥94 |
| LED lifetime | 50,000 h | 50,000 h | 50,000 h | 50,000 h |
| Beam Angle Options | 16°, 33°, 40° | Variable from 18° to 50° | Variable from 12° to 45° | 12°, 18°, 40°, 60° |
| Weight | 2.4 Kg (5.2 lbs) | 2.1 Kg (4.6 lbs) | 2.1 Kg (4.6 lbs) | 1.2 Kg (2.6 lbs) |
| Power supply | 120 - 277 Vac | 84 - 264 Vac | 120 - 277 Vac | 120 - 277 Vac |
| Control/Dimming | Manual, DALI, Bluetooth | Manual, DALI, BT, RDM, DMX | Manual, DALI, Bluetooth | Manual, DALI, Bluetooth |
| Standard Colors | Black, White | Black, White | Black, White | Black, White |
| Dimensions | 218 mm x ø83 mm 8.6"x ø3.2" | 209-269 mm x ø121 mm 8.2"-10.6"x ø4.8" | 240-280 mm x ø83 mm 9.4"-11"x ø3.2" | 118 mm x ø83 mm 4.6"x ø3.2" |
| STATUS | On request | On stock | On stock | On stock |

| Feature | APPLAUD | ADMIRE | RESPECT |
|--------------------|---|---|---|
| Type | Framer/Gobo | Variable Beam | Spot |
| Light Source | Fixed White LED | Fixed White LED | Fixed White LED |
| Rated Power | 30W | 30W | 30W |
| Luminous Flux | 2200 lm (@ 2700K) 2250 lm (@ 3000K) 2300 lm (@ 4000K) | 2200 lm (@ 2700K) 2250 lm (@ 3000K) 2300 lm (@ 4000K) | 2200 lm (@ 2700K) 2250 lm (@ 3000K) 2300 lm (@ 4000K) |
| CCT Options | 2700K 3000K 4000K | 2700K 3000K 4000K | 2700K 3000K 4000K |
| CRI | ≥97 | ≥97 | ≥97 |
| LED lifetime | 50,000 h | 50,000 h | 50,000 h |
| Beam Angle Options | 16°, 33°, 40° | Variable from 12° to 45° | 12°, 18°, 40°, 60° |
| Weight | 2.4 Kg (5.2 lbs) | 2.1 Kg (4.6 lbs) | 1.2 Kg (2.6 lbs) |
| Power supply | 120 - 277 Vac | 120 - 277 Vac | 120 - 277 Vac |
| Control/Dimming | Manual, DALI, Bluetooth | Manual, DALI, Bluetooth | Manual, DALI, Bluetooth |
| Standard Colors | Black, White | Black, White | Black, White |
| Dimensions | 218 mm x ø83 mm 8.6"x ø3.2" | 240-280 mm x ø83 mm 9.4"-11"x ø3.2" | 118 mm x ø83 mm 4.6"x ø3.2" |
| STATUS | On request | On stock | On stock |

FIND YOUR MODEL WITH THE ACL CONFIGURATOR

There are several parameters which determine the best model of ART Centric Lighting unit for a particular application. The first is the quality of the light, i.e. with fixed or adjustable colour temperature. The second is the type of beam required, i.e. spotlight, shaped beam or variable beam. Then there is the best optical unit for the projection distance, and the type of control system required. Lastly, you have to consider the colour of the external casing of the unit itself.



To choose the unit you need from among the many available, you can use the ACL CONFIGURATOR application available at www.art-centric-lighting-com: it will guide you step by step in choosing the model that best suits your needs.

Moreover, if you still have doubts about the choice between two or more models, you can compare them using the ACL COMPARATOR (available at www.art-centric-lighting-com).